CS 343: Artificial Intelligence

Reinforcement Learning

Prof. Yuke Zhu

The University of Texas at Austin

[These slides were created by Dan Klein and Pieter Abbeel for CS188 Intro to AI at UC Berkeley. All CS188 materials are available at http://ai.berkeley.edu.]

Announcements

Homework 3: Games

Due Monday, 2/28 at 11:59 pm

Project 2: Multi-Agent Pacman

Due Wednesday, 3/2 at 11:59 pm

Homework 4: MDPs

Due Monday, 3/7 at 11:59 pm

Reinforcement Learning



Reinforcement Learning

- Still assume a Markov decision process (MDP):
  - A set of states $s \in S$
  - A set of actions (per state) A
  - A model T(s,a,s')
  - A reward function R(s,a,s')
- Still looking for a policy $\pi(s)$

Cool

Warm

Overheated

- New twist: don't know T or R
  - I.e. we don't know which states are good or what the actions do
  - Must actually try actions and states out to learn

Value Iteration

- Bellman equations characterize the optimal values:

$$V^*(s) = \max_a \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma V^*(s') \right]$$



- Value iteration computes them:

$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma V_k(s') \right]$$

- Value iteration is just a fixed point solution method
  - … though the V_k vectors are also interpretable as time-limited values

Reinforcement Learning



- Basic idea:
  - Receive feedback in the form of rewards
  - Agent's utility is defined by the reward function
  - Must (learn to) act so as to maximize expected rewards
  - All learning is based on observed samples of outcomes!

Example: Learning to Walk

Initial (19.5 cm/s)

After learning (28 cm/s)

Example: Atari from raw pixels

Example: Robot manipulation



Offline (MDPs) vs. Online (RL)



Offline Solution

Online Learning

Model-Based Learning

- Model-Based Idea:
  - Learn an approximate model based on experiences
  - Solve for values as if the learned model were correct

- Step 1: Learn empirical MDP model
  - Count outcomes s' for each s, a
  - Normalize to give an estimate of $\hat{T}(s, a, s')$
  - Discover each $\hat{R}(s, a, s')$ when we experience (s, a, s')

- Step 2: Solve the learned MDP
  - For example, use value iteration, as before

Example: Model-Based Learning

Input Policy π



Assume: $\gamma = 1$

Observed Episodes (Training)

Episode 1

B, east, C, -1
C, east, D, -1
D, exit, x, +10

Episode 2

B, east, C, -1
C, east, D, -1
D, exit, x, +10

Episode 3

E, north, C, -1
C, east, D, -1
D, exit, x, +10

Episode 4

E, north, C, -1
C, east, A, -1
A, exit, x, -10

Learned Model

$\hat{T}(s, a, s')$

T(B, east, C) =
T(C, east, D) =
T(C, east, A) =
...

$\hat{R}(s, a, s')$

R(B, east, C) =
R(C, east, D) =
R(D, exit, x) =
...

Example: Model-Based Learning

Input Policy π



Assume: $\gamma = 1$

Observed Episodes (Training)

Episode 1

B, east, C, -1
C, east, D, -1
D, exit, x, +10

Episode 2

B, east, C, -1
C, east, D, -1
D, exit, x, +10

Episode 3

E, north, C, -1
C, east, D, -1
D, exit, x, +10

Episode 4

E, north, C, -1
C, east, A, -1
A, exit, x, -10

Learned Model

$\hat{T}(s, a, s')$

T(B, east, C) = 1.00
T(C, east, D) = 0.75
T(C, east, A) = 0.25
...

$\hat{R}(s, a, s')$

R(B, east, C) = -1
R(C, east, D) = -1
R(D, exit, x) = +10
...

Example: Expected Age

Goal: Compute expected age of CS 343 students

Known P(A)

$$E[A] = \sum_a P(a) \cdot a \qquad = 0.35 \times 20 + \ldots$$

Without P(A), instead collect samples [a_1, a_2, … a_N]

Unknown P(A): "Model Based"

$$\hat{P}(a) = \frac{\text{num}(a)}{N}$$

$$E[A] \approx \sum_a \hat{P}(a) \cdot a$$

Why does this work? Because eventually you learn the right model.

Unknown P(A): "Model Free"

$$E[A] \approx \frac{1}{N} \sum_i a_i$$

Why does this work? Because samples appear with the right frequencies.

Model-Free Learning



Passive Reinforcement Learning



Passive Reinforcement Learning

- Simplified task: policy evaluation
  - Input: a fixed policy $\pi(s)$
  - You don't know the transitions T(s,a,s')
  - You don't know the rewards R(s,a,s')
  - Goal: learn the state values



- In this case:
  - Learner is "along for the ride"
  - No choice about what actions to take
  - Just execute the policy and learn from experience
  - This is NOT offline planning! You actually take actions in the world.

Direct Evaluation

- Goal: Compute values for each state under π
- Idea: Average together observed sample values
  - Act according to π
  - Every time you visit a state, write down what the sum of discounted rewards turned out to be
  - Average those samples
- This is called direct evaluation

Example: Direct Evaluation

Input Policy π



Assume: $\gamma = 1$

Observed Episodes (Training)

Episode 1

B, east, C, -1
C, east, D, -1
D, exit, x, +10

Episode 2

B, east, C, -1
C, east, D, -1
D, exit, x, +10

Episode 3

E, north, C, -1
C, east, D, -1
D, exit, x, +10

Episode 4

E, north, C, -1
C, east, A, -1
A, exit, x, -10

Output Values



Problems with Direct Evaluation

- What's good about direct evaluation?
  - It's easy to understand
  - It doesn't require any knowledge of T, R
  - It eventually computes the correct average values, using just sample transitions
- What bad about it?
  - It wastes information about state connections
  - Each state must be learned separately
  - So, it takes a long time to learn

Output Values



If B and E both go to C under this policy, how can their values be different?

Why Not Use Policy Evaluation?

- Simplified Bellman updates calculate V for a fixed policy:
  - Each round, replace V with a one-step-look-ahead layer over V

$$V_0^{\pi}(s) = 0$$

$$V_{k+1}^{\pi}(s) \leftarrow \sum_{s'} T(s, \pi(s), s')[R(s, \pi(s), s') + \gamma V_k^{\pi}(s')]$$



  - This approach fully exploited the connections between the states
  - Unfortunately, we need T and R to do it!

- Key question: how can we do this update to V without knowing T and R?
  - In other words, how to we take a weighted average without knowing the weights?

Sample-Based Policy Evaluation?

- We want to improve our estimate of V by computing these averages:

$$V^{\pi}_{k+1}(s) \leftarrow \sum_{s'} T(s, \pi(s), s')[R(s, \pi(s), s') + \gamma V^{\pi}_{k}(s')]$$

- Idea: Take samples of outcomes s' (by doing the action!) and average

$$sample_1 = R(s, \pi(s), s'_1) + \gamma V^{\pi}_{k}(s'_1)$$
$$sample_2 = R(s, \pi(s), s'_2) + \gamma V^{\pi}_{k}(s'_2)$$
$$\cdots$$
$$sample_n = R(s, \pi(s), s'_n) + \gamma V^{\pi}_{k}(s'_n)$$

$$V^{\pi}_{k+1}(s) \leftarrow \frac{1}{n} \sum_{i} sample_i$$



Almost! But we can't rewind time to get sample after sample from state s.

Temporal Difference Learning



Temporal Difference Learning

- Big idea: learn from every experience!
  - Update V(s) each time we experience a transition (s, a, s', r)
  - Likely outcomes s' will contribute updates more often



- Temporal difference learning of values
  - Policy still fixed, still doing evaluation!
  - Move values toward value of whatever successor occurs: running average

Sample of V(s): $sample = R(s, \pi(s), s') + \gamma V^{\pi}(s')$

Update to V(s): $V^{\pi}(s) \leftarrow (1-\alpha)V^{\pi}(s) + (\alpha)sample$

Same update: $V^{\pi}(s) \leftarrow V^{\pi}(s) + \alpha(sample - V^{\pi}(s))$

Exponential Moving Average

- Exponential moving average
  - The running interpolation update: $\bar{x}_n = (1-\alpha) \cdot \bar{x}_{n-1} + \alpha \cdot x_n$
  - Makes recent samples more important:

$$\bar{x}_n = \frac{x_n + (1-\alpha) \cdot x_{n-1} + (1-\alpha)^2 \cdot x_{n-2} + \dots}{1 + (1-\alpha) + (1-\alpha)^2 + \dots}$$

  - Forgets about the past (distant past values were wrong anyway)

- Decreasing learning rate (alpha) can give converging averages

Example: Temporal Difference Learning

States



Assume: γ = 1, α = 1/2

Observed Transitions

B, east, C, -2



C, east, D, -2





$$V^{\pi}(s) \leftarrow (1-\alpha)V^{\pi}(s) + \alpha\left[R(s,\pi(s),s') + \gamma V^{\pi}(s')\right]$$

Problems with TD Value Learning

- TD value leaning is a model-free way to do policy evaluation, mimicking Bellman updates with running sample averages
- However, if we want to turn values into a (new) policy, we're sunk:

$$\pi(s) = \arg\max_a Q(s,a)$$

$$Q(s,a) = \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma V(s') \right]$$



- Idea: learn Q-values, not values
- Makes action selection model-free too!

Active Reinforcement Learning



Active Reinforcement Learning

- Full reinforcement learning: optimal policies (like value iteration)
  - You don't know the transitions T(s,a,s')
  - You don't know the rewards R(s,a,s')
  - You choose the actions now
  - Goal: learn the optimal policy / values



- In this case:
  - Learner makes choices!
  - Fundamental tradeoff: exploration vs. exploitation
  - This is NOT offline planning! You actually take actions in the world and find out what happens…

Detour: Q-Value Iteration

- Value iteration: find successive (depth-limited) values
  - Start with $V_0(s) = 0$, which we know is right
  - Given V_k, calculate the depth k+1 values for all states:

$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma V_k(s') \right]$$

- But Q-values are more useful, so compute them instead
  - Start with $Q_0(s,a) = 0$, which we know is right
  - Given Q_k, calculate the depth k+1 q-values for all q-states:

$$Q_{k+1}(s,a) \leftarrow \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma \max_{a'} Q_k(s',a') \right]$$

Q-Learning

- Q-Learning: sample-based Q-value iteration

$$Q_{k+1}(s,a) \leftarrow \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma \max_{a'} Q_k(s',a') \right]$$

- Learn Q(s,a) values as you go
  - Receive a sample (s,a,s',r)
  - Consider your old estimate: $Q(s,a)$
  - Consider your new sample estimate:

$$sample = R(s,a,s') + \gamma \max_{a'} Q(s',a')$$

  - Incorporate the new estimate into a running average:

$$Q(s,a) \leftarrow (1-\alpha)Q(s,a) + (\alpha)\,[sample]$$



Demo of Q-Learning -- Gridworld



Demo of Q-Learning -- Crawler



Q-Learning Properties

- Amazing result: Q-learning converges to optimal policy -- even if you're acting suboptimally!

- This is called off-policy learning

- Caveats:
  - You have to explore enough
  - You have to eventually make the learning rate small enough
  - … but not decrease it too quickly
  - Basically, in the limit, it doesn't matter how you select actions (!)